

# Solid State Relays Cross-Reference Product List

## About This Document

Guaranteed-for-life Opto 22 solid state relays (SSRs) can in many cases be substituted for other manufacturers' SSRs. This technical note lists part number matches and notes differences with other manufacturers' products.

If you have any questions on the list or on Opto 22 SSRs, please contact Opto 22.  
 Phone: 800-321-6786 (toll-free in the U.S. and Canada) or 951-695-3000  
 Email: [systemseng@opto22.com](mailto:systemseng@opto22.com)

*NOTE: Although this information is accurate to the best of our knowledge as of the document date, Opto 22 accepts no liability for the completeness or accuracy of the information nor for the consequences of any actions taken on the basis of the information provided. Please let us know if you find inaccuracies.*

## Cross-Reference Product List

For details on Opto 22 SSRs, see the [SSR Data Sheet, form #0859](#).

Opto 22	Crydom	Gordos	Crouzet	Notes
<a href="#">120A10</a>	A1210	G120A10	--	
<a href="#">120A25</a>	A1225	G120A25	--	
<a href="#">240A10</a>	A2410	G240A10	84134001	
<a href="#">240A25</a>	A2425	G240A25	84134011	
<a href="#">240A45</a>	A2450	G240A45	84134021	Opto 22 is rated at 45 A.
<a href="#">120D3</a>	--	--	--	No cross.
<a href="#">120D10</a>	D1210	G120D10	--	
<a href="#">120D25</a>	D1225	G120D25	--	
<a href="#">120D45</a>	D1240	G120D45	--	Opto 22 is rated at 45 A.
<a href="#">240D3</a>	--	--	--	No cross.
<a href="#">240D10</a>	D2410	G240D10	84134000	
<a href="#">240Di10</a>	D2410	G240D10	84134000	Opto 22 part has LED indicator.
<a href="#">240D25</a>	D2425	G240D25	84134010	
<a href="#">240Di25</a>	D2425	G240D25	84134010	Opto 22 part has LED indicator.
<a href="#">240D30-HS</a>	D2425	G240D25		Opto 22 part has integrated heat sink and is rated at 30 A.
<a href="#">240D45</a>	D2450	G240D45	84134020	Opto 22 is rated at 45 A.
<a href="#">240Di45</a>	D2450	G240D45	84134020	Opto 22 part has LED indicator and is rated at 45 A.
<a href="#">380D25</a>	--	--	--	No cross.*

Opto 22	Crydom	Gordos	Crouzet	Notes
380D45	--	--	--	No cross.*
480D10-12	HD4812	G480D10	--	
480D15-12	--	G480D10	--	
480D25-12	HD4825	G480D25	--	
480D25-HS	HD4825	G480D25	--	Opto 22 has an integrated heatsink.
480D45-12	HD4850	G480D50	--	Opto 22 part is rated at 45 A.
575D15-12	--	--	84134100	Opto 22 operating voltage is 100-600 VAC, rated at 15 A.
575D45-12	HD6025	G575D50	84134120	Opto 22 operating voltage is 100-600 VAC, rated at 45 A.
575D30-HS	HD6025	G575D25	84134110	Opto 22 part has integrated heatsink, operating voltage 100-600 VAC, rated at 30 A.
575Di45-12	HD6050	G575D50	--	Opto 22 has LED indicator, operating voltage 100-600 VAC, rated at 45 A.
MP120D2	--	--	--	No cross.
MP120D4	MP120D3	--	GA8-6B02	
MP240D2	--	GA8-6B02	GA8-6B02	
MP240D4	MP240D3	GA8-6B02	GA8-6B02	
MP380D4	MCX380D5	--	--	Opto 22 is rated at 4 A.
P120D2	--	GA1-6B02	GA1-6B02	
P120D4	--	GA1-6B02	GA1-6B02	
P240D2	--	GA1-6B02	GA1-6B02	
P240D4	--	GA1-6B02	GA1-6B02	
Z120D10	EZ240D12	--	--	Opto 22 is rated at 10 A.
Z240D10	EZ240D12	--	--	Opto 22 is rated at 10 A.
DC60P	--	--	--	No cross.
DC60MP	MPDCD3, MODC5	M-ODC5A	--	
DC200P	--	--	--	No cross.
DC200MP	MODC5A	M-ODC5A	--	
DC60S3	DC60S3	GT60D10	--	Opto 22 is rated at 3 A.
DC60S5	DC60S5	GT60D10	84134750	Opto 22 is rated at 5 A.

\* If your distributor is temporarily out of stock on Opto 22 380D25 or 380D45, you can substitute Opto 22 480D25-12 or 480D45-12.